

SAFETY FINISH WAX (NON BUFF)



DESCRIPTION: SAFETY FINISH WAX (NON BUFF) is designed to act as a sealer-finish for most porous and non-porous flooring to improve wearability. SAFETY FINISH WAX (NON BUFF) is fortified with metallic/acrylic polymer, combined with a creative balance of thermo plastic resins, poly waxes, and leveling agents. This finish has a spectacular gloss after an initial application of three coats and wet gloss look is obtained by high speed buffing.

BENEFITS and FEATURES:

- Designed for ultra-high-speed burnishing or high-speed spray buff systems
- Flexibility to withstand repeated burnishing without film degradation
- “Wet look” gloss
- Exceptional resistance to powdering
- Long term durability
- Superior mark resistance

DIRECTIONS FOR USE: Before application, remove old finish, wax, and/or soil with a heavy-duty stripper. Rinse floor thoroughly with clean water and allow to completely dry. Apply SAFETY FINISH WAX (NON BUFF) in uniform, thin-to-medium coats using a clean synthetic finish mop or applicator system. For sealed floors, apply two (2) coats. For unsealed floors, apply three (3) coats. Allow each coat to thoroughly dry between coats, usually 30 to 50 minutes. It is recommended waiting 24 hours or longer before allowing heavy equipment usage. Additional coats may be applied periodically or as required to maintain finish. Deep scrub the surface prior to reapplying maintenance coats.

SPECIFICATION:

Color.....	Milky White Emulsion
Fragrance.....	Acrylic
pH.....	7.5 – 8.5
Specific Gravity.....	1.017 – 1.037
Film Color	Clear
Detergent Resistance	Excellent
Stability.....	Minimum 2 years
Coverage	1,500 – 2,000 sq. ft./gal.
Volatile Organic Compound (VOC).....	< 5 g/L

Refer to the Safety Data Sheet (SDS) and product label for additional information including Hazard and Precautionary statements, first aid measures, and storage and handling.



NSN 6850-01-434-4412

Honolulu, Hawaii | Toll Free Phone: 808.590.2053 | Fax: 888.227.7211 | www.coast-products.com

